

<b>Table 2.1</b>	Relative electrical and thermal conductivities of common conductor materials . . . . .	6–7
<b>Table 2.2</b>	Diameters for copper and aluminum conductors . . . . .	9–10
<b>Table 2.3</b>	Tensile strength of copper wire . . . . .	11
<b>Table 2.4</b>	Strand classes . . . . .	12–13
<b>Table 2.5</b>	Standard nominal diameters and cross-sectional areas of solid copper wire . . . . .	14–15
<b>Table 2.6</b>	Class B concentric-lay-stranded copper conductors . . . . .	15–17
<b>Table 2.7</b>	Class H rope-lay-stranded copper conductors . . . . .	17–18
<b>Table 2.8</b>	Class K rope-lay-stranded copper conductors . . . . .	19
<b>Table 2.9</b>	Class M rope-lay-stranded copper conductors . . . . .	20
<b>Table 2.10</b>	Aluminum 1350 solid round wire . . . . .	21–22
<b>Table 2.11</b>	Class B concentric-lay-stranded aluminum 1350 conductors . . . . .	22–23
<b>Table 2.12</b>	Concentric-lay-stranded aluminum conductors—coated-steel reinforced (ACSR) . . . .	24–25
<b>Table 3.1</b>	K-1 color sequence . . . . .	34
<b>Table 3.2</b>	K-2 color sequence . . . . .	35
<b>Table 3.3</b>	K-3 color sequence . . . . .	35
<b>Table 3.4</b>	K-4 color sequence . . . . .	36
<b>Table 3.5</b>	K-5 color sequence . . . . .	37–38
<b>Table 3.6</b>	Common multiconductor color code (Belden standard) . . . . .	38
<b>Table 3.7</b>	Common multipair color code (Belden standard) . . . . .	39
<b>Table 3.8</b>	Telecommunication cable color code (solid colors) . . . . .	40
<b>Table 3.9</b>	Telecommunication cable color code (band marked) . . . . .	40
<b>Table 3.10</b>	Properties of thermoplastic insulation & jacket materials . . . . .	41–43
<b>Table 3.11</b>	Properties of thermoset insulation & jacket materials . . . . .	44–45
<b>Table 3.12</b>	Properties of EPR compared with those of XLPE . . . . .	46
<b>Table 3.13</b>	Halogen content in typical insulation and jacket materials . . . . .	47
<b>Table 3.14</b>	LOI of common wire and cable materials . . . . .	48
<b>Table 3.15</b>	Dielectric constant of common wire and cable materials . . . . .	48
<b>Table 4.1</b>	Power cable shielding . . . . .	51
<b>Table 4.2</b>	Foil shielding . . . . .	52
<b>Table 4.3</b>	Copper braid shields . . . . .	53
<b>Table 4.4</b>	Spiral shields . . . . .	54
<b>Table 5.1</b>	ICEA recommended thickness of interlocked armor . . . . .	56
<b>Table 6.1</b>	Flexible cord type designations . . . . .	61–62
<b>Table 6.2</b>	Color code for thermocouple wire . . . . .	65
<b>Table 6.3</b>	Color code for thermocouple extension wire . . . . .	65
<b>Table 6.4</b>	High temperature cable ratings chart . . . . .	66–67

## INDEX OF TABLES

---

<b>Table 6.5</b>	Twisted pair cable performance categories . . . . .	73
<b>Table 6.6</b>	IBM cable types . . . . .	75
<b>Table 6.7</b>	A comparison of loose tube and tight buffer optical fiber cable . . . . .	83
<b>Table 6.8</b>	Tray cable listings and markings . . . . .	84
<b>Table 7.1</b>	DC resistance of plated copper conductors . . . . .	87–90
<b>Table 7.2</b>	DC and AC resistance of class B copper conductors, ohms per 1000 feet . . . . .	90–91
<b>Table 7.3</b>	Temperature correction factors for Table 7.2 . . . . .	91
<b>Table 7.4</b>	DC and AC resistance of class B aluminum conductors, ohms per 1000 feet . . . . .	92
<b>Table 7.5</b>	Temperature correction factors for Table 7.4 . . . . .	93
<b>Table 7.6</b>	Reactance and impedance at 60 Hz for single copper conductor cables installed in air, buried or in separate nonmetallic conduits . . . . .	93–94
<b>Table 7.7</b>	AC/DC resistance ratio at 60 hertz . . . . .	95–96
<b>Table 7.8</b>	Temperature correction factors for the resistance of copper conductors . . . . .	96
<b>Table 7.9</b>	Phase-to-phase voltage drop per amp per 100 ft of circuit for a 3-phase, 60 Hz system operating at 60°C with copper conductors . . . . .	97
<b>Table 7.10</b>	Phase-to-phase voltage drop per amp per 100 ft of circuit for a 3-phase, 60 Hz system operating at 60°C with aluminum conductors . . . . .	98
<b>Table 7.11</b>	Maximum short circuit current for copper shielding tape (amperes) . . . . .	101
<b>Table 7.12</b>	400 & 800 Hz ampacity factors for 600 volt cables with class B strand, installed with minimum triangular spacing in air or in nonmetallic conduit . . . . .	102
<b>Table 7.13</b>	Basic impulse level (BIL) ratings . . . . .	104
<b>Table 8.1</b>	Maximum number of conductors in electrical metallic tubing . . . . .	108–111
<b>Table 8.2</b>	Maximum cable diameters for permissible conduit fill . . . . .	111
<b>Table 8.3</b>	Dimensions and maximum allowable percent fill of electrical metallic tubing (EMT) . . . . .	112
<b>Table 8.4</b>	Bend multipliers for pulling tension calculations . . . . .	116
<b>Table 8.5</b>	Maximum sidewall pressure (SWP) for power cables . . . . .	117–118
<b>Table 8.6</b>	Minimum bending radii for cables without metallic shielding . . . . .	118
<b>Table 8.7</b>	Messenger breaking strength in lbs. . . . .	123
<b>Table 8.8</b>	Messenger weight in lbs./1000 ft . . . . .	123
<b>Table 8.9</b>	Maximum core weight in lbs./ft . . . . .	123
<b>Table 8.10</b>	Galvanized steel strand/physical specifications . . . . .	124
<b>Table 8.11</b>	Spacings for conductor supports . . . . .	125
<b>Table 8.12</b>	Maximum DC test voltages for shielded power cables . . . . .	128
<b>Table 8.13</b>	AEIC hipot test voltages . . . . .	129
<b>Table 9.1</b>	Connections for the first four pairs of UTP cable . . . . .	139
<b>Table 9.2</b>	3M Scotchlok connector dimensions . . . . .	141
<b>Table 9.3</b>	3M Scotchlok lug dimensions . . . . .	142–144
<b>Table 10.1</b>	Minimum drum diameter for wire and cable . . . . .	152–153

<b>Table 10.2</b>	Capacities and dimensions of standard shipping reels 22"–66" in diameter . . . . .	154–155
<b>Table 10.3</b>	Capacities and dimensions of standard shipping reels 78"–108" in diameter . . . . .	156–157
<b>Table 10.4</b>	Typical small reel dimensions . . . . .	158
<b>Table 11.1</b>	Fire safety test methods . . . . .	193
<b>Table 11.2</b>	NEC fire test summary . . . . .	194
<b>Table 11.3</b>	Comparison of vertical cable tray tests . . . . .	195–196
<b>Table 11.4</b>	NEC Article 725–Summary of remote control, signaling and power-limited circuit types . . . . .	202
<b>Table 11.5</b>	Symbols of international organizations . . . . .	203–204
<b>Table 12.1</b>	Conductor size conversion: metric to English and English to metric . . . . .	206–209
<b>Table 12.2</b>	Circular measurements–diameter, circumference, area . . . . .	210–214
<b>Table 12.3</b>	Conversion factors . . . . .	215–217
<b>Table 12.4</b>	Degrees centigrade (Celsius) vs. degrees Fahrenheit . . . . .	218
<b>Table 12.5</b>	KVA to amperes . . . . .	219–220
<b>Table 13.1</b>	Electrical properties of circuits . . . . .	222
<b>Table 13.2</b>	Resistance, inductance, and capacitance in AC circuits . . . . .	223
<b>Table 13.3</b>	Series and parallel connections . . . . .	224
<b>Table 13.4</b>	Engineering notation . . . . .	224
<b>Table 13.5</b>	Engineering notation . . . . .	225
<b>Table 13.6</b>	Diameter of multiconductor cables . . . . .	225
<b>Table 13.7</b>	Determination of largest possible conductor in cable interstices . . . . .	226
<b>Table 13.8</b>	Concentric stranded conductor diameter from wire diameter . . . . .	226
<b>Table 14.1</b>	CENELEC harmonized approvals in the European Union . . . . .	233
<b>Table 14.2</b>	DC resistance of Class 1 (solid) copper conductors . . . . .	237
<b>Table 14.3</b>	DC resistance and stranding of Class 2 copper conductors . . . . .	237–238
<b>Table 14.4</b>	DC resistance and stranding of Class 5 (flexible) copper conductors . . . . .	238–239
<b>Table 14.5</b>	DC resistance and stranding of Class 6 (highly flexible) copper conductors . . . . .	239–240
<b>Table 14.6</b>	EU supply voltages . . . . .	240
<b>Table 14.7</b>	EU power plug configurations . . . . .	240
<b>Table 14.8</b>	Austrian supply voltage . . . . .	241
<b>Table 14.9</b>	Austrian plug configuration . . . . .	241
<b>Table 14.10</b>	Belgian supply voltages . . . . .	243
<b>Table 14.11</b>	Belgian plug configurations . . . . .	243
<b>Table 14.12</b>	Danish supply voltage . . . . .	244
<b>Table 14.13</b>	Danish plug configuration . . . . .	244
<b>Table 14.14</b>	French supply voltages . . . . .	246
<b>Table 14.15</b>	French plug configurations . . . . .	246

## INDEX OF TABLES

---

<b>Table 14.16</b>	DIN 47100 color code for single conductors . . . . .	247
<b>Table 14.17</b>	DIN 47100 color code for paired conductors . . . . .	248
<b>Table 14.18</b>	German supply voltage . . . . .	249
<b>Table 14.19</b>	German plug configurations . . . . .	249
<b>Table 14.20</b>	Irish supply voltage . . . . .	250
<b>Table 14.21</b>	Irish plug configurations . . . . .	250
<b>Table 14.22</b>	Italian supply voltage . . . . .	252
<b>Table 14.23</b>	Italian plug configurations . . . . .	252
<b>Table 14.24</b>	Dutch supply voltage . . . . .	253
<b>Table 14.25</b>	Dutch plug configurations . . . . .	253
<b>Table 14.26</b>	Norwegian supply voltage . . . . .	254
<b>Table 14.27</b>	Norwegian plug configurations . . . . .	254
<b>Table 14.28</b>	Portuguese supply voltage . . . . .	255
<b>Table 14.29</b>	Portuguese plug configurations . . . . .	255
<b>Table 14.30</b>	Spanish supply voltages . . . . .	256
<b>Table 14.31</b>	Spanish plug configurations . . . . .	256
<b>Table 14.32</b>	Swedish supply voltage . . . . .	257
<b>Table 14.33</b>	Swedish plug configurations . . . . .	258
<b>Table 14.34</b>	Swiss supply voltage . . . . .	259
<b>Table 14.35</b>	Swiss plug configurations . . . . .	259
<b>Table 15.1</b>	United Kingdom supply voltage . . . . .	270
<b>Table 15.2</b>	United Kingdom plug configurations . . . . .	270
<b>Table 16.1</b>	Mexican supply voltage . . . . .	273
<b>Table 16.2</b>	Mexican plug configuration . . . . .	273
<b>Table 17.1</b>	Some Canadian cable types, conditions of use and maximum conductor temperatures . . . . .	279–286
<b>Table 17.2</b>	Canadian supply voltage . . . . .	287
<b>Table 17.3</b>	Canadian plug configurations . . . . .	287
<b>Table 18.1</b>	Australian supply voltages . . . . .	292
<b>Table 18.2</b>	Australian plug configuration . . . . .	292
<b>Table 18.3</b>	Limiting temperatures for Australian insulated cables . . . . .	292–293
<b>Table 18.4</b>	Singapore supply voltage . . . . .	294
<b>Table 18.5</b>	Singapore plug configurations . . . . .	294
<b>Table 18.6</b>	Japanese plug configuration . . . . .	295

<b>Figure 1.1</b>	Three phase wye (star) Three wire . . . . .	3
<b>Figure 1.2</b>	Three phrase delta Three wire . . . . .	3
<b>Figure 1.3</b>	Three phase star Four wire, grounded neutral . . . . .	3
<b>Figure 1.4</b>	Three phase wye (star) Three wire, grounded neutral . . . . .	3
<b>Figure 1.5</b>	Three phase delta Four wire, grounded midpoint . . . . .	3
<b>Figure 2.1</b>	Concentric strand . . . . .	7
<b>Figure 2.2</b>	Rope strand . . . . .	8
<b>Figure 2.3</b>	Sector conductor . . . . .	8
<b>Figure 2.4</b>	Segmental conductor . . . . .	8
<b>Figure 2.5</b>	Annular conductor . . . . .	8
<b>Figure 2.6</b>	Compact concentric strand . . . . .	8
<b>Figure 2.7</b>	Comparative sizes and shapes of 1000 kcmil conductors . . . . .	9
<b>Figure 3.1</b>	Nominal temperature range of cable polymers . . . . .	46
<b>Figure 4.1</b>	Typical copper tape shielded power cable . . . . .	51
<b>Figure 4.2</b>	Foil shield . . . . .	52
<b>Figure 4.3</b>	“Z” fold foil shield . . . . .	52
<b>Figure 4.4</b>	Dual braid shield construction on a multipair cable . . . . .	53
<b>Figure 4.5</b>	Copper braid construction on a coaxial cable . . . . .	53
<b>Figure 4.6</b>	Spiral or serve shield . . . . .	54
<b>Figure 5.1</b>	Continuously corrugated and welded (CCW) armor . . . . .	56
<b>Figure 6.1</b>	A typical 600 volt control cable . . . . .	63
<b>Figure 6.2</b>	Control cable with overall shield . . . . .	63
<b>Figure 6.3</b>	Control cable with individually shielded pairs and an overall shield . . . . .	63
<b>Figure 6.4</b>	A typical thermocouple circuit . . . . .	65
<b>Figure 6.5</b>	Typical tape shielded 15 kV power cable . . . . .	68
<b>Figure 6.6</b>	Typical wire shielded 15 kV power cable . . . . .	69
<b>Figure 6.7</b>	Typical coaxial cable . . . . .	70
<b>Figure 6.8</b>	Flexible coax . . . . .	72
<b>Figure 6.9</b>	Semirigid coax . . . . .	72
<b>Figure 6.10</b>	Triaxial . . . . .	72
<b>Figure 6.11</b>	Dual coaxial . . . . .	72
<b>Figure 6.12</b>	A typical twinaxial cable . . . . .	72
<b>Figure 6.13</b>	Optical fiber types . . . . .	80
<b>Figure 6.14</b>	Optical fiber attenuation . . . . .	81
<b>Figure 6.15</b>	Optical fiber cable designs . . . . .	82
<b>Figure 7.1</b>	Maximum conductor short circuit current for copper cables . . . . .	99

## INDEX OF FIGURES

---

<b>Figure 7.2</b>	Maximum conductor short circuit current for aluminum cables	100
<b>Figure 7.3</b>	Current ratings for electronic cables	103
<b>Figure 8.1</b>	How to calculate clearance	114
<b>Figure 8.2</b>	Calculating minimum bending radius	119
<b>Figure 8.3</b>	Cable feed-in setups	120–122
<b>Figure 8.4</b>	Connections for testing insulation resistance between one wire and ground	130
<b>Figure 8.5</b>	Connections for testing insulation resistance between one wire and all other wires	131
<b>Figure 8.6</b>	Moisture removal equipment	132
<b>Figure 9.1</b>	BNC connectors	136
<b>Figure 9.2</b>	SMA series coax connectors for semirigid cable	137
<b>Figure 9.3</b>	SMA series coax connectors for flexible cable	137
<b>Figure 9.4</b>	UHF series coax connectors	138
<b>Figure 9.5</b>	N series coax connectors	138
<b>Figure 9.6</b>	F series coax connector	138
<b>Figure 9.7</b>	RJ-45 (8 pin) modular plug	140
<b>Figure 9.8</b>	Wiring methods A and B on an RJ-45 modular jack	140
<b>Figure 9.9</b>	3M Scotchlok connector	141
<b>Figure 9.10</b>	3M Scotchlok lugs	142
<b>Figure 9.11</b>	Terminal stud size chart in English and metric units	145
<b>Figure 9.12</b>	ST type connector	147
<b>Figure 9.13</b>	FDDI connector	148
<b>Figure 9.14</b>	SMA connector	148
<b>Figure 9.15</b>	Biconic connector	149
<b>Figure 10.1</b>	Reel terminology	152
<b>Figure 10.2</b>	Winding cables smaller than 1/2" in diameter	159
<b>Figure 10.3</b>	Winding cables larger than 1/2" in diameter	159
<b>Figure 10.4</b>	Fastening the trailing end of the cable	160
<b>Figure 10.5</b>	Rewinding of interlocked armor cable	161
<b>Figure 10.6</b>	Proper handling of cable reels	162
<b>Figure 11.1</b>	UL 910 Steiner tunnel test	196
<b>Figure 11.2</b>	UL 1666 Riser flame test	197
<b>Figure 11.3</b>	UL 1581 Vertical tray flame test	198
<b>Figure 11.4</b>	UL 1581 VW-1 flame test	199
<b>Figure 11.5</b>	Typical UL marks	200
<b>Figure 14.1</b>	CENELEC cable identification code	234
<b>Figure 14.2</b>	Example of a CENELEC cable identification code	235

**A**

**ABNT** ..... 274

**Acceptance testing** ..... 127

**AC circuits**, resistance, inductance, and capacitance in ..... 223

**AC/DC resistance ratio**, at 60 Hertz ..... 95

**ACSR**. *See* Aluminum strand properties

**AEE** ..... 256

**AENC** ..... 256

**Aerospace wire** ..... 78

**AFN** ..... 245

**Agencies**. *See* Regulatory and approval agencies; Standards and specifications

**Aircore cables** ..... 76

**Alternating Current (AC)** ..... 3

**Aluminum conductors**, DC and AC resistance of Class B ..... 92–93

**Aluminum strand properties** ..... 21–25

**ACSR** ..... 24–25

    Class B Aluminum ..... 22–23

    solid aluminum ..... 21–22

**Ambient temperature** ..... 68

**Ampacity** ..... 3, 68

    at 400 and 800 Hz ..... 102

    of power cables ..... 104

**Ampere** ..... 2

**ANCE** ..... 272

**Annular conductor** ..... 8

**Armor** ..... 55–57

    basket weave ..... 57

    cables ..... 70

    continuously corrugated and welded (CCW) ..... 56

    interlocked ..... 56

    lead sheath ..... 57

    wire serve ..... 57

**Asia and Pacific Rim**, standards and specifications in ..... 290–295

**ASTM** ..... 169–171

**Attenuation** ..... 81

**Austel** ..... 291

**Australia**, standards in ..... 290–293

**Austrian standards** ..... 241

**B**

**Bandwidth** ..... 81

**BASEC** ..... 264

**Basic Impulse Level (BIL) ratings** ..... 104

**Basket weave armor** ..... 57

**Basket weave pulling grip** ..... 113

**BBC** ..... 264

**Belden electronic color code** ..... 38–39

**Belgian standards** ..... 242–243

**Bellcore** ..... 172, 173

**Bending radii** ..... 118–119

**Bend multipliers** ..... 116

**Bends**, in duct and conduit runs ..... 114

**Biconic connectors** ..... 149

**BIL**. *See* Basic Impulse Level ratings

**BNC connectors** ..... 136

**BNFL** ..... 265

**Braid shield** ..... 53

**Brazil**, standards and specifications in ..... 274

**BRB** ..... 265

**Britain**. *See* United Kingdom

**British Coal** ..... 265

**British Telecom** ..... 266

**Broken fiber** ..... 133

**BSI** ..... 262–264

**Buffers** ..... 82, 83

**Bunch strand** ..... 8

**C**

**Cable**. *See* Cable types; Wire and cable packaging

**Cable interstices**, largest possible conductor in ..... 226

**Cable types** ..... 59–84

    armored power and control ..... 70

    in Canada ..... 279–286

    coaxial ..... 70–72

    construction and building wire ..... 62

    control ..... 63

    current ratings for electronic ..... 103

    electronic ..... 52–54, 70–75

    fiber optic connectors ..... 146

    flexible ..... 61, 62

    high temperature wire and cable ..... 66–67

    IBM Cabling System ..... 75

    instrumentation ..... 63

    interlocked armor ..... 113

    large pair count ..... 39

    lead-sheathed ..... 113

    military ..... 78–79

    mining ..... 62

    multiconductor ..... 225

    nonmetallic sheathed ..... 113

    optical fiber ..... 80–83

    portable power and control ..... 61–62

    power ..... 50–51, 67–69, 104

    shipboard ..... 79–80

    telephone ..... 76–77

    thermocouple ..... 64–65

    tray cables ..... 83

    twinx cable ..... 72

    UTP and STP ..... 73–74

**Canada**

    cable types in ..... 279–286

    fire ratings in ..... 288

## GENERAL INDEX

- standards and specifications in . . . . 276–278  
 supply voltage and plug  
 configurations in . . . . . 287
- CANENA** . . . . . 174
- Capacitance**, in AC circuits . . . . . 223
- Categories**, of twisted pair cable  
 performance . . . . . 73, 74
- CATV systems** . . . . . 138
- CCW armor**. See Continuously corrugated  
 and welded armor
- CEBEC** . . . . . 203, 242
- CEI** . . . . . 251
- CEN** . . . . . 240
- CENELEC** . . . . . 203, 232–240  
 cable identification code . . . . . 234–235  
 color codes . . . . . 236  
 copper conductors . . . . . 237–240  
 harmonized approvals in European  
 Union . . . . . 233
- CESI** . . . . . 251
- Chlorinated polyethylene (CPE)** . . . . . 30
- CIGRE** . . . . . 245
- Circuits**  
 AC . . . . . 223  
 electrical properties of . . . . . 222
- Cladding layer** . . . . . 80
- Clearance in duct and conduit** . . . . . 114
- CMP** . . . . . See also Aluminum conductors;  
 Coatings; Copper conductors . . . . . 6
- CNET** . . . . . 245
- Coatings**  
 nickel . . . . . 10  
 silver plated . . . . . 10  
 tin . . . . . 10
- Coaxial cable** . . . . . 70–72  
 capacitance of . . . . . 227
- Coaxial connectors** . . . . . 136–138
- Colombia**, standards and specifications in . . . 274
- Color coding**  
 of insulation and jacket materials . . . . 33–40  
 for telecommunication . . . . . 39  
 for thermocouple wire . . . . . 65
- Compact strand** . . . . . 8
- Compressed strand** . . . . . 9
- Concentric strand** . . . . . 7
- Conductive shield** . . . . . 50
- Conductor diameter**, from wire diameter . . . 226
- Conductors** See also Aluminum conductors;  
 Coatings; Copper conductors . . . . . 6  
 aluminum strand properties . . . . . 21–25  
 in cable interstices . . . . . 226  
 coatings for . . . . . 10  
 copper strands . . . . . 12–20  
 copper wire . . . . . 11  
 resistance and weight of . . . . . 223
- strand types . . . . . 7–10  
 “tip” and “ring” . . . . . 76
- Conductor shield (strand shield)** . . . . . 50
- Conductor size** . . . . . 68
- Conduit fill** . . . . . 108–112
- Connections**, series and parallel . . . . . 224
- Connectors**  
 biconic . . . . . 149  
 BNC . . . . . 136  
 coaxial . . . . . 136–138  
 FC . . . . . 149  
 FDDI . . . . . 148  
 fiber optic . . . . . 146–149  
 F series . . . . . 138  
 mini BNC . . . . . 149  
 N series . . . . . 138  
 power . . . . . 141–146  
 SC . . . . . 146, 147  
 SHV . . . . . 137  
 SMA . . . . . 137, 148  
 ST . . . . . 146, 147  
 telecommunications . . . . . 139–140  
 3M . . . . . 141–144  
 TNC . . . . . 137  
 UHF . . . . . 138
- Constants**. See Formulas and constants
- Construction and building wire** . . . . . 62  
 RHH . . . . . 62  
 RHW-2 . . . . . 62  
 SER . . . . . 62  
 SE-U . . . . . 62  
 TFFN . . . . . 62  
 TFN . . . . . 62  
 thermostat . . . . . 62  
 THHN . . . . . 62  
 THW . . . . . 62  
 THW-2 . . . . . 62  
 THWN . . . . . 62  
 THWN-2 . . . . . 62  
 USE . . . . . 62  
 USE-2 . . . . . 62  
 XHHW . . . . . 62  
 XHHW-2 . . . . . 62
- Continuously corrugated and welded (CCW)  
 armor** . . . . . 56
- Control cables** . . . . . 63
- Conversion tables** . . . . . 205–220  
 circular measurements—diameter,  
 circumference, area . . . . . 210–215  
 KVA to amperes . . . . . 219–220  
 length, weight, area, power . . . . . 215–217  
 metric to English . . . . . 206–209  
 temperature . . . . . 218
- Copper braid shield** . . . . . 53

**Copper conductors.** *See also* Conductors  
 DC and AC resistance of Class B . . . . 90–91  
 DC resistance of plated . . . . . 87–90

**Copper strand properties** . . . . . 12–20  
 Class B Copper . . . . . 15–17  
 Class H Copper . . . . . 17–18  
 Class K Copper . . . . . 19  
 Class M Copper . . . . . 20  
 solid copper . . . . . 14–15

**Copper tape shields** . . . . . 51

**Copper wire** . . . . . 11

**Core of optical fibers**  
 diameter of . . . . . 81  
 glass . . . . . 80

**COTNNIE** . . . . . 272

**Coulomb** . . . . . 2

**COVENIN** . . . . . 273

**Crosslinked polyethylene (XLP, XLPE)** . . . . 31  
 properties of . . . . . 46

**CSA** . . . . . 83, 198, 203, 276–278

**CSA standards.** *See* Standards and specifications

**CSP.** *See* Hypalon

**Current** . . . . . 2  
 short circuit . . . . . 68

**Current-carrying capacity** . . . . . 68

**D**

**Danish standards** . . . . . 244

**DC and AC resistance**  
 of Class B aluminum conductors . . . . 92–93  
 of Class B copper conductors . . . . . 90–91

**DC maintenance testing** . . . . . 127

**DC resistance, of plated copper conductors** 87–90

**DEMKO** . . . . . 203, 244

**Department of the Environment (UK)** . . . . 266

**Department of Transport (UK)** . . . . . 267

**Dielectric constant** . . . . . 31  
 of common wire and cable materials . . . . 48

**DIN** . . . . . 247

**DKE** . . . . . 249

**Drain wire** . . . . . 52

**Drum diameter** . . . . . 152–153

**Dual coaxial cable** . . . . . 72

**Dutch standards** . . . . . 252–253

**E**

**EA** . . . . . 268

**ECTFE.** *See* Halar

**EIA** . . . . . 175–177

**Electrical characteristics** . . . . . 85–104  
 AC/DC resistance ratio at 60 Hertz . . . 95–96  
 basic impulse level (BIL) ratings . . . . . 104  
 conductor short circuit current . . . . . 98, 99, 100  
 DC/AC resistance of class B aluminum  
 conductors . . . . . 92–93

DC/AC resistance of class B copper  
 conductors . . . . . 90–91

DC resistance of plated copper  
 conductors . . . . . 87–90

electronic cable ratings . . . . . 103

power cable ampacity . . . . . 104

reactance and impedance at  
 60 Hertz . . . . . 93–94

resistance and ampacity at 400 and  
 800 Hz . . . . . 102

shield short-circuit current . . . . . 101

temperature correction factors . . . . . 96

voltage drop . . . . . 97, 98

**Electrical Inspectorate (Finland)** . . . . . 203

**Electrical metallic tubing (EMT)** . . . . . 108  
*See also* Installation and testing

**Electrical properties, of circuits** . . . . . 222

**Electrical systems** . . . . . 3

**Electricity** . . . . . 2

**Electricity Trust of South Australia** . . . . . 203

**Electromotive force (EMF)** . . . . . 2

**Electronic cable** . . . . . 70–75  
 coaxial . . . . . 70–72  
 ratings for . . . . . 103  
 twinax . . . . . 72

**Electronic cable shields** . . . . . 50, 52–54  
 copper braid . . . . . 53  
 foil . . . . . 52  
 spiral (serve) . . . . . 54

**Electrons** . . . . . 2

**Emission shield** . . . . . 50

**EMT.** *See* Electrical metallic tubing

**End seals** . . . . . 115

**Engineering notation** . . . . . 224–225

**England.** *See* United Kingdom

**EPR.** *See* Ethylene propylene rubber

**ERA Technology Ltd.** . . . . . 267

**ESI.** *See* EA

**ETFE.** *See* Tefzel

**Ethylene propylene rubber (EP, EPR, or EPDM)** . . . . . 31  
 properties of . . . . . 41

**ETSA** . . . . . 291

**Europe** . . . . . 232–259  
 Austrian standards . . . . . 241  
 Belgian standards . . . . . 242–243  
 Danish standards . . . . . 244  
 Dutch standards . . . . . 252–253  
 EU standards . . . . . 232–240  
 French standards . . . . . 245–246  
 German standards . . . . . 247–249  
 Irish standards . . . . . 250  
 Italian standards . . . . . 251–252  
 Norwegian standards . . . . . 254

## GENERAL INDEX

Portuguese standards	255
Spanish standards	256
Swedish standards	257–258
Swiss standards	258–259
United Kingdom standards	262–270
<b>European Union (EU) standards</b>	232–240
CEN	240
CENELEC	232–240
supply voltages	240
<b>Exchange cables</b>	76
<b>Extension grade wire</b>	64

### F

<b>FAA</b>	177
<b>Fault locating</b>	129, 133
<b>FC connectors</b>	149
<b>FDDI (Fiber Distributed Data Interface)</b>	
connector	148
<b>Fiberglass</b>	32
<b>Fiber optic connectors</b>	146–149
<b>Fiber optic testing</b>	133
<b>Fiber selection, for optical fiber cables</b>	81
<b>Filled cables</b>	76
<b>Fire ratings, in Canada</b>	288
<b>Fire safety tests</b>	83, 193–199
<b>Flame retardant EP</b>	31
<b>Flexible coax</b>	71
<b>Flexible cords</b>	61, 62
<b>Fluoropolymers</b>	28
<b>Foil shields</b>	52
<b>Formulas and constants</b>	221–227
coaxial capacitance	227
conductor diameter from wire diameter	226
electrical properties of circuits	222
engineering notation	224–225
maximum size conductor in interstices	226
multiconductor cable diameter	225
resistance, inductance, and capacitance	
in AC circuits	223
resistance and weight of conductors	223
series and parallel connections	224
<b>French standards</b>	245–246
<b>FREP</b>	31
<b>Frequency range of coaxial connectors</b>	136
<b>F series connectors</b>	138

### G

<b>Galvanized steel strand/physical specifications</b>	124
<b>German standards</b>	247–249
<b>Glass core of optical fibers</b>	80
<b>Ground check (GC) conductor</b>	62
<b>Grounded systems</b>	67

### H

<b>Halar (ECTFE)</b>	29
<b>Halogen content, in insulation and jacket materials</b>	47
<b>Handling. See Receiving, handling and storage</b>	
<b>HAR approval</b>	232
<b>High temperature wire and cable</b>	66–67
<b>Hipot testing</b>	126–129
<b>Hypalon (CSP)</b>	32

### I

<b>IBM Cabling System</b>	75
<b>IBN/NBT</b>	242
<b>ICEA</b>	33, 178–179, 198
<b>ICONTEC</b>	274
<b>IEC</b>	179–181
<b>IEE</b>	268
<b>IEEE</b>	182–183, 198
<b>IEEE 802.5 networks</b>	75
<b>Impedance</b>	70
at 60 Hertz	93, 94
<b>IMQ</b>	251
<b>Indoor cables</b>	76–77
<b>Inductance, in AC circuits</b>	223
<b>Installation and testing</b>	105–133
conduit fill	108–112
fault locating	129
hipot testing	126–129
installation methods	120–122
LAN cable testing	133
megger testing	130–131
moisture removal	131–132
overhead messengers	123–124
pulling	113–119
receiving, handling and storage	107
vertical suspension	125
<b>Installation methods</b>	120–122
<b>Instrumentation cable</b>	63
<b>Insulated Cable Engineers Association (ICEA)</b>	3
<b>Insulation and jacket materials</b>	27–48, 77
color coding	33–40
fibrous coverings	32
telecommunication color coding	39, 40
thermoplastics	28–30
thermosets	30–32
types and applications	28–32
<b>Insulation level</b>	67
<b>Insulation Resistance (IR)</b>	130
<b>Insulation shield. See Outer shield</b>	
<b>Interlocked armor cable</b>	56, 113
rewinding	161
<b>International</b>	
organizations	203–204, 229–295
<b>Interstices</b>	226

IPQ	255
Irish standards	250
IR tests	130
ISA	184
ISO	184, 203
Istituto Italiano del Marchio	203
Italian standards	251–252
ITS	257
ITU	184

**J**

Jacket materials	77
<i>See</i> Insulation and jacket materials	
Jacks, modular	140
Jamming	115
Japan, standards in	295
JIS	295

**K**

Kema, N.V.	203, 252
K-fiber	32
Kynar (PVDF)	29

**L**

LANs. <i>See</i> Local area networks	
Latin and South America, standards in	272–274
Lead sheath armor	57
Lead-sheathed cables	113
Leakage current	127, 128
Limiting oxygen index (LOI)	48
Local area networks (LANs) cable testing	74, 133
LOI. <i>See</i> Limiting oxygen index	
London Underground Limited	268
Loose buffer	82
Low voltage systems	3
Lugs and connectors	141–145

**M**

Megger testing	130–131
Messengers. <i>See</i> Overhead messengers	
Mexico, standards and specifications in	272–273
Microbending	133
MIL-C-24640 cable	79–80
MIL-C-24643 cable	79–80
MIL-C-915 cable	79–80
Military wire and cable types	78–79
Mini BNC connectors	149
Minimum bending radius	118–119
Mining cable	62
Ministry of Defense (UK)	269
Modular plugs and jacks	140
Moisture removal	131–132
MPF (mine power feeder) cables	62

MSHA	185
Multiconductor cable, diameter of	225
Multipair color code	39

**N**

NCB. <i>See</i> British Coal	
NEC (National Electrical Code)	3, 33, 108, 194, 201–202
NEC (Netherlands Electro-Technical Committee)	253
NEMA	185–186
NEMKO	203, 254
Neoprene (CP)	31
NFFPA	187
NIST	187
NOM	272
Nonmetallic-sheathed cables	113
Norwegian standards	254
Notation, engineering	224–225
NSAI	250
N series connectors	138
NTRA	254

**O**

Ohm	2
Ohm's Law	3
Operating temperature	68
Optical fiber cables fiber selection	80–83, 81
selecting	82–83
Optical power meters	133
Optical Time Domain Reflectometers (OTDRs)	133
Organizations. <i>See also</i> Standards and specifications	
domestic	165–193
international	203–204, 229–295
OTDRs. <i>See</i> Optical Time Domain Reflectometers	
Outer shield (insulation shield)	50–51
Outside cables	76
ÖVE	203, 241
Overhead messengers	123–124

**P**

Pacific Rim. <i>See</i> Asia and Pacific Rim	
Packaging, of wire and cable	151–162
Parallel connections	224
PE. <i>See</i> Polyethylene	
PFA. <i>See</i> Teflon	
Plastic cladding	80
Plenum cables	77
Plugs, modular	140
Polyethylene (PE)	29
Polyolefins (PO)	29
Polypropylene (PP)	30
Polyurethane (PUR)	30

## GENERAL INDEX

**Polyvinyl chloride (PVC)** . . . . . 28  
**Portable cords**  
   SJ . . . . . 61  
   SJO . . . . . 61  
   SJOW-A . . . . . 61  
   SJTO . . . . . 61  
   SO . . . . . 61  
   SOOW-A . . . . . 61  
   SOW . . . . . 61  
   SOW-A . . . . . 61  
   STO . . . . . 61  
**Portuguese standards** . . . . . 255  
**Power cable** . . . . . 67–69  
   ampacity of . . . . . 104  
   conductor size . . . . . 68  
   short circuit current . . . . . 68  
   special considerations . . . . . 69  
   voltage drop considerations . . . . . 69  
   voltage rating . . . . . 67  
**Power cable shields** . . . . . 50  
   conductor (strand) . . . . . 50  
   outer (insulation) . . . . . 50–51  
**Power connectors** . . . . . 141–146  
**Preassembled aerial cable** . . . . . 113  
**Proof testing** . . . . . 127  
**PTFE.** *See* Teflon  
**PTT** . . . . . 258  
**Pulling** . . . . . 113–119  
**Pulling eyes** . . . . . 113  
**Pulling lubricants** . . . . . 117  
**Pulling swivel** . . . . . 113  
**Pulling tension** . . . . . 113  
   calculation of . . . . . 115–116  
**PUR.** *See* Polyurethane  
**PVC.** *See* Polyvinyl chloride  
**PVDF.** *See* Kynar

## R

**Radar** . . . . . 129  
**Ratio, jam** . . . . . 115  
**REA** . . . . . 188  
**Reactance, at 60 Hertz** . . . . . 93, 94  
**Receiving, handling and storage** . . . . . 107  
**Reels**  
   handling . . . . . 159–162  
   moving and lifting . . . . . 162  
   size . . . . . 152–158  
**Reflectometers**  
   optical time domain . . . . . 133  
   time domain . . . . . 133  
**Refractive index** . . . . . 80  
**Regulatory and approval agencies** . . . . . 200–204  
   National Electrical Code (NEC) . . . . . 201–202  
   UL . . . . . 200

**Resistance** . . . . . 2  
   in AC circuits . . . . . 223  
   AC/DC ratio at 60 Hertz . . . . . 95  
   of conductors . . . . . 223  
   at 400 and 800 Hz . . . . . 102  
   temperature correction factors for . . . . . 96  
**RJ-11 modular plugs and jacks** . . . . . 140  
**RJ-45 modular plugs and jacks** . . . . . 140  
**Rope strand** . . . . . 8

## S

**SAA** . . . . . 290–291  
**SAE** . . . . . 188  
**SCC** . . . . . 278  
**SC (subscriber connector) connectors** . . . . . 147  
**Scotland.** *See* United Kingdom  
**Sector conductor** . . . . . 8  
**Segmental conductor** . . . . . 8  
**Semi-conductive shield** . . . . . 50  
**Semirigid coax** . . . . . 71  
**SEMKO** . . . . . 204, 257  
**Series connections** . . . . . 224  
**Serve shields.** *See* Spiral (serve) shields  
**SEV** . . . . . 259  
**Shielded twisted pair (STP) cable** . . . . . 73, 74  
**Shields**  
   conductor . . . . . 50  
   electronic cable . . . . . 52–54  
   outer . . . . . 50–51  
   power cable . . . . . 50–51  
**Shipboard cables** . . . . . 78, 79–80  
**Shipping reels** . . . . . 154–157  
**Short circuit current** . . . . . 68  
   maximum conductor . . . . . 98–100  
   maximum shield . . . . . 101  
**Shovel (SHD) cables** . . . . . 62  
**SHV connectors** . . . . . 137  
**Sidewall pressure (SWP)** . . . . . 114, 117–118  
**Signal leakage** . . . . . 52  
**Silicone** . . . . . 32  
**Singapore, standards in** . . . . . 293–294  
**SISIR** . . . . . 293  
**SMA connectors** . . . . . 137, 148  
**SNV** . . . . . 258  
**South America.** *See* Latin and South America  
**Spanish standards** . . . . . 256  
**Specifications.** *See* Standards and specifications  
**Spiral (serve) shields** . . . . . 54  
**Standards and specifications** . . . . . 163–204  
   ASTM . . . . . 169–171  
   Belden electronic color code . . . . . 38–39  
   Bellcore . . . . . 172, 173  
   Brazilian . . . . . 274  
   CANENA . . . . . 174  
   Colombian . . . . . 274

continental European . . . . .	232–259		
CSA . . . . .	83, 198		
EIA . . . . .	175–177		
European Union (EU) . . . . .	232–240		
FAA . . . . .	177		
fire safety tests . . . . .	193–199		
galvanized steel . . . . .	124		
ICEA . . . . .	33, 178–179, 198		
IEC . . . . .	179–181		
IEEE . . . . .	182–183, 198		
ISA . . . . .	184		
ISO . . . . .	184		
ITS . . . . .	257		
ITU . . . . .	184		
Mexican . . . . .	272–273		
MSHA . . . . .	185		
NEC . . . . .	33, 194		
NEMA . . . . .	185–186		
NFPA . . . . .	187		
NIST . . . . .	187		
organizations . . . . .	165–193		
ÖVE . . . . .	241		
REA . . . . .	188		
regulatory and approval agencies . . . . .	200–204		
SAE . . . . .	188		
UL . . . . .	83, 84, 189–190, 196–197, 198, 199		
in United Kingdom . . . . .	262–270		
U.S. government . . . . .	190, 191		
U.S. military . . . . .	191–193		
Venezuelan . . . . .	273		
vertical cable tray tests . . . . .	195–196		
<b>Standing-wave ratio (VSWR)</b> . . . . .	71		
<b>Station wire</b> . . . . .	76		
<b>ST connectors</b> . . . . .	147		
<b>Steel wires</b> . . . . .	57		
<b>Storage.</b> <i>See</i> Receiving, handling and storage			
<b>STP.</b> <i>See</i> Shielded twisted pair cable			
<b>Stranding</b>			
annular . . . . .	8		
bunch . . . . .	8		
compact . . . . .	8		
compressed . . . . .	9		
concentric . . . . .	7		
copper strand properties . . . . .	12–20		
rope . . . . .	8		
sector . . . . .	8		
segmental . . . . .	8		
types of . . . . .	7–10		
<b>Strand shield.</b> <i>See</i> Conductor shield			
<b>Stress control layer</b> . . . . .	50		
<b>Stud sizes</b> . . . . .	145		
<b>Submarine cable</b> . . . . .	57		
<b>Supply voltage and plug configurations,</b> in Canada . . . . .	287		
			<i>See also</i> Standards and specifications
<b>Suspension, vertical</b> . . . . .	125		
<b>Swedish standards</b> . . . . .	257–258		
<b>Swiss standards</b> . . . . .	258–259		
<b>SWP.</b> <i>See</i> Sidewall pressure			
			<b>T</b>
<b>TDR.</b> <i>See</i> Time Domain Reflectometer			
<b>Technische Prüfanstalten des SEV's</b> . . . . .	204		
<b>Teflon</b> . . . . .	28–29		
<b>Tefzel (ETFE)</b> . . . . .	29		
<b>Telecommunication color coding</b> . . . . .	39, 40		
<b>Telecommunications connectors</b> . . . . .	139–140		
<b>Telephone cables</b> . . . . .	76–77		
<b>Temperature</b>			
ambient . . . . .	68		
operating . . . . .	68		
operating range . . . . .	71		
<b>Temperature correction factors, for</b> resistance . . . . .	96		
<b>Tension</b>			
limitations of . . . . .	113–114		
pulling . . . . .	113, 115–116		
<b>Testing.</b> <i>See</i> Installation and testing			
<b>TFE.</b> <i>See</i> Teflon			
<b>Thermal properties</b> . . . . .	46		
<b>Thermocouple junction</b> . . . . .	64		
<b>Thermocouple wire</b> . . . . .	64		
Type E (chromel vs. constantan) . . . . .	64		
Type J (iron vs. constantan) . . . . .	64		
Type K (chromel vs. alumel) . . . . .	64		
Type N (nicrosil vs. nisil) . . . . .	64		
Type T (copper vs. constantan) . . . . .	64		
<b>Thermoplastic elastomer (TPE)</b> . . . . .	30		
<b>Thermoplastics</b> . . . . .	28–30		
fluoropolymers . . . . .	28		
Halar (ECTFE) . . . . .	29		
Kynar (PVDF) . . . . .	29		
polyethylene (PE) . . . . .	29		
polyolefins (PO) . . . . .	29		
polypropylene (PP) . . . . .	30		
polyurethane (PUR) . . . . .	30		
polyvinyl chloride (PVC) . . . . .	28		
properties of . . . . .	41–43		
Teflon . . . . .	28–29		
Teflon TFE . . . . .	29		
Tefzel (ETFE) . . . . .	29		
thermoplastic elastomer (TPE) . . . . .	30		
<b>Thermosets</b> . . . . .	30–32		
chlorinated polyethylene (CPE) . . . . .	30		
crosslinked polyethylene (XLP, XLPE) . . . . .	31		
ethylene propylene rubber (EP, EPR, or EPDM) . . . . .	31		
Hypalon (CSP) . . . . .	32		
neoprene (CP) . . . . .	31		

## GENERAL INDEX

properties of . . . . . 44–45  
 silicone . . . . . 32  
**3M power connectors** . . . . . 141–146  
**Three phase delta Three wire** . . . . . 3  
**Three phase star Four wire,**  
     grounded neutral . . . . . 3  
**Three phase wye (star) Three wire** . . . . . 3  
**3-sheave pulleys** . . . . . 115  
**Tight buffer** . . . . . 82  
**Time Domain Reflectometer (TDR)** . . . . . 129, 133  
**“Tip” and “ring” conductors** . . . . . 76  
**TNC connectors** . . . . . 136, 137  
**TPE.** *See* Thermoplastic elastomer  
**TPR.** *See* Thermoplastic elastomer  
**Tray cables** . . . . . 83–84  
**Treeing in insulations** . . . . . 50  
**Triaxial cable** . . . . . 72  
**Tubing** . . . . . 79  
**Twinax cable** . . . . . 72  
**Type CM cable** . . . . . 77  
**Type CMR cable** . . . . . 77  
**TZV VS** . . . . . 259

**U**

**UHF connectors** . . . . . 138  
**UL (Underwriters Laboratories)** . . . . .  
     . . . . . 83, 84, 189–190, 196–197, 204  
     *See also* Standards and specifications  
     UL 1581 Vertical tray flame test . . . . . 198, 199  
**UNEL** . . . . . 251  
**Ungrounded systems** . . . . . 67  
**Union Technique de L'Electricite** . . . . . 204  
**United Kingdom, standards and**  
     specifications in . . . . . 262–270  
**Unshielded twisted pair (UTP)**  
     **cable** . . . . . 73, 74, 139  
**U.S. government, standards and**  
     specifications . . . . . 190, 191  
**U.S. military** . . . . . 191–193  
**UTE** . . . . . 245  
**UTP.** *See* Unshielded twisted pair cable

## V

**VDE** . . . . . 232, 248  
**VDE-Prüfstelle** . . . . . 204  
**Velocity of propagation** . . . . . 71  
**Venezuela, standards and specifications in** . . . . . 273  
**Vertical cable tray tests** . . . . . 195–196  
**Vertical suspension** . . . . . 125  
**Vertical tray flame test** . . . . . 83  
**Vinyl** . . . . . 28  
**Volt** . . . . . 2  
**Voltage, test** . . . . . 128–129  
**Voltage drop** . . . . . 69, 97, 98  
**Voltage rating** . . . . . 67, 71  
**VSWR** . . . . . 71

## W

**Water.** *See* Moisture removal  
**Weight, of conductors** . . . . . 223  
**Wire.** *See* Cable types; Construction and  
     building wire; Wire and cable packaging  
**Wire and cable packaging** . . . . . 151–162  
     reel handling . . . . . 159–162  
     reel size . . . . . 152–158  
**Wire diameter, from conductor diameter** . . . . . 226  
**Wire serve armor** . . . . . 57  
**Wire shields** . . . . . 51  
**Wire wrap** . . . . . 78

## X

**XLP, XLPE.** *See* Crosslinked polyethylene

## Z

**“Z” fold shield** . . . . . 52