

## **FIT® Shelf Life Guide**

Below you will find the shelf lives for all of our FIT Heat-Shrink Tubing products and select Wire Management products.

**Products not listed below do not have a specified or documented shelf life.**

Please Note: The storage temperature range for all of these products is **65°F-95°F**.

*\*Shelf lives are based upon manufacturer's recommendations*

Product Type	Shrink Ratio	Material Type	Shelf Life (Yrs)
FIT-105	2:1	PVC	1
FIT-221	2:1	Polyolefin	5
FIT-221B	2:1	Polyolefin	5
FIT-221V	2:1	Polyolefin	5
FIT-260	2:1	Polyolefin	2
FIT-295	2:1	Polyolefin	5
FIT-300	3:1	Polyolefin	3
FIT-321	3:1	Polyolefin	3
FIT-321V	3:1	Polyolefin	2
FIT-350	2:1	PVDF	5
FIT-375	2:01	PVDF, Modified	5
FIT-400	1.2:1	FEP	4
FIT-500	1.5:1	TFE	4
FIT-600	1.75:1	Chlorinated Polyolefin	1
FIT-621	6:1	Polyolefin	2
FIT-650	2:1	Fluoroelastomer	2
FIT-700	3:1	Polyolefin	2
FIT-750	2:1	Polyolefin	3
FIT-CAP	2:1	Polyolefin	2
FIT-CRIMP	2:1	Nylon	2
FIT-FAB	2:1	Polyester	2
FIT-FLEX	1.7:1	Silicone	2
FIT-PRINT	3:1	Polyolefin	3
FIT-RP	3:1	Polyolefin	2
FIT-SLV-(12-16)	---	PVDF	2
FIT-SLV-(22-26)	---	PVDF	5
CST*	---	Cu & Adhesive	2
Lacing Cords*	---	Various	1yr after opening
TY2001	---	Silicon	1